



Warm your life





OR-15T
■ With 24 hours timer

OR-15TF
■ With 24 hours timer
■ With 400W ceramic fan heater

OR-15/OR15T/OR-15TF

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
5	1000W	300x165x660	1898	2180
7	1500W	370x165x660	1530	1734
9	2000W	450x165x660	1264	1440
11	2000W	530x165x660	1060	1226
11	2500W	530x165x660	1060	1226
13	2500W	610x165x660	912	1062

General features:

- 3 different heat settings
- Adjustable thermostat control
- Operating switches with indication lights
- Automatic thermal cut off for extra safety
- High quality construction with tough durable finish
- Handle and castors for an easy movement
- 24 hours segmented dial timer (Only for OR-15T/OR-15TF)
- 400W ceramic fan heater (Only for OR-15TF)
- Fin Size:150mmx580mm



OR-07T
■ With 24 hours timer

OR-07TF
■ With 24 hours timer
■ With 400W ceramic fan heater

OR-07/OR-07T/OR-07TF

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
5	1000W	300x165x660	1898	2180
7	1500W	370x165x660	1530	1734
9	2000W	450x165x660	1264	1440
11	2000W	530x165x660	1060	1226
11	2500W	530x165x660	1060	1226
13	2500W	610x165x660	912	1062

General features:

- 3 different heat settings
- Adjustable thermostat control
- Operating switches with indication lights
- Automatic thermal cut off for extra safety
- High quality construction with tough durable finish
- Handle and castors for an easy movement
- 24 hours segmented dial timer (Only for OR-07T/OR-07TF)
- 400W ceramic fan heater (Only for OR-07TF)
- Fin Size:150mmx580mm



OR-06T
■ With 24 hours timer

OR-06TF
■ With 24 hours timer
■ With 400W ceramic fan heater

OR-06/OR-06T/OR-06TF

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
5	1000W	300x165x660	1898	2180
7	1500W	370x165x660	1530	1734
9	2000W	450x165x660	1264	1440
11	2000W	530x165x660	1060	1226
11	2500W	530x165x660	1060	1226
13	2500W	610x165x660	912	1062

General features:

- 3 different heat settings
- Adjustable thermostat control
- Operating switches with indication lights
- Automatic thermal cut off for extra safety
- High quality construction with tough durable finish
- Handle and castors for an easy movement
- 24 hours segmented dial timer (Only for OR-06T/OR-06TF)
- 400W ceramic fan heater (Only for OR-06TF)
- Fin Size:150mmx580mm



OR-16T
■ With 24 hours timer

OR-16TF
■ With 24 hours timer
■ With 400W ceramic fan heater

OR-16/OR-16T/OR-16TF

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
5	1000W	300x165x660	1898	2180
7	1500W	370x165x660	1530	1734
9	2000W	450x165x660	1264	1440
11	2000W	530x165x660	1060	1226
11	2500W	530x165x660	1060	1226
13	2500W	610x165x660	912	1062

General features:

- 3 different heat settings
- Adjustable thermostat control
- Operating switches with indication lights
- Automatic thermal cut off for extra safety
- High quality construction with tough durable finish
- Handle and castors for an easy movement
- 24 hours segmented dial timer (Only for OR-16T/OR-16TF)
- 400W ceramic fan heater (Only for OR-16TF)
- Fin Size:150mmx580mm



OR-05



OR-05T

■ With 24 hours timer

OR-05/OR-05T

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
5	1000W	300x165x660	1898	2180
7	1500W	370x165x660	1530	1734
9	2000W	450x165x660	1264	1440
11	2000W	530x165x660	1060	1226
11	2500W	530x165x660	1060	1226
13	2500W	610x165x660	912	1062

General features:

- 3 different heat settings
- Adjustable thermostat control
- Operating switches with indication lights
- Automatic thermal cut off for extra safety
- High quality construction with tough durable finish
- Handle and castors for an easy movement
- 24 hours segmented dial timer (Only for OR-05T)
- Fin Size:150mmx580mm



OR-02



OR-02T

■ With 24 hours timer

OR-02/OR-02T

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
5	1000W	300x165x660	1898	2180
7	1500W	370x165x660	1530	1734
9	2000W	450x165x660	1264	1440
11	2000W	530x165x660	1060	1226
11	2500W	530x165x660	1060	1226
13	2500W	610x165x660	912	1062

General features:

- 3 different heat settings
- Adjustable thermostat control
- Operating switches with indication lights
- Automatic thermal cut off for extra safety
- High quality construction with tough durable finish
- Handle and castors for an easy movement
- 24 hours segmented dial timer (Only for OR-02T)
- Fin Size:150mmx580mm



OR-121



OR-121T

■ With 24 hours timer

OR-121/OR-121T

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
5	1000W	310x135x660	2242	2582
7	1500W	370x135x660	1936	2174
9	2000W	450x135x660	1506	1768
11	2000W	530x135x660	1278	1508
11	2500W	530x135x660	1278	1508
13	2500W	610x135x660	1095	1304

General features:

- 3 different heat settings
- Adjustable thermostat control
- Operating switches with indication lights
- Automatic thermal cut off for extra safety
- High quality construction with tough durable finish
- Handle and castors for an easy movement
- 24 hours segmented dial timer (Only for OR-121T)
- Fin Size:120mmx580mm



OR-120



OR-120T

■ With 24 hours timer

OR-120/OR-120T

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
5	1000W	310x135x660	2242	2582
7	1500W	370x135x660	1936	2174
9	2000W	450x135x660	1506	1768
11	2000W	530x135x660	1278	1508
11	2500W	530x135x660	1278	1508
13	2500W	610x135x660	1095	1304

General features:

- 3 different heat settings
- Adjustable thermostat control
- Operating switches with indication lights
- Automatic thermal cut off for extra safety
- High quality construction with tough durable finish
- Handle and castors for an easy movement
- 24 hours segmented dial timer (Only for OR-120T)
- Fin Size:120mmx580mm



OA-7



OR-3

OA-7/OR-3

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
5	1000W	300x165x660	1898	2180
7	1500W	370x165x660	1530	1734
9	2000W	450x165x660	1264	1440
11	2000W	530x165x660	1060	1226
11	2500W	530x165x660	1060	1226
13	2500W	610x165x660	912	1062

General features:

- 3 different heat settings
- Adjustable thermostat control
- Operating switches with indication lights
- Automatic thermal cut off for extra safety
- High quality construction with tough durable finish
- Handle and castors for an easy movement
- Fin Size:150mmx580mm

Mini Oil Filled Radiator

OFR17/OR320

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
6	500W	290x135x400	3600	4240
7	600W	330x135x400	3150	3710
9	900W	410x135x400	2610	3070

General features:

- Mini-type for personal use
- Energy-efficient heat emission
- Form 6 fins to 9 fans
- Adjustable thermostat
- Over heating protection
- Gree environmental conducting oil
- Power indicator light
- Fin Size:125mmx320mm



OFR17



OR320



PH-ET07

PH-ET07E

PH-ET07

- Power:425W
- Heating element:Heating wires
- Overheat protection
- Wall mounted or floor stand
- IPX4 water proof
- Meas(mm):600x600x110
- Qty 20'/40'/40'HQ:1032/2160/2588pcs

PH-ET07E

- Power:425W
- Heating element:Heating wires
- Overheat protection
- Wall mounted or floor stand
- LED display
- One week timer and 24 hours timer
- IPX4 water proof
- Meas(mm):600x600x110
- Qty 20'/40'/40'HQ:1032/2160/2588pcs



PH-ET07H

PH-ET07TD

PH-ET07H

- Power:425W
- Heating element:Heating wires
- Overheat protection
- Wall mounted or floor stand
- IPX4 water proof
- Meas(mm):600x600x110
- Qty 20'/40'/40'HQ:1032/2160/2588pcs

PH-ET07TD

- Power:425W
- Heating element:Heating wires
- Overheat protection
- Wall mounted or floor stand
- LED display
- One week timer and 24 hours timer
- IPX4 water proof
- Meas(mm):600x600x110
- Qty 20'/40'/40'HQ:1032/2160/2588pcs



PH-ET07TM

PH-ET08

PH-ET07TM

- Power:425W
- Heating element:Heating wires
- Overheat protection
- Wall mounted or floor stand
- 24 hours timer
- IPX4 water proof
- Meas(mm):600x600x110
- Qty 20'/40'/40'HQ:1032/2160/2588pcs

PH-ET08

- Power:425W
- Heating element:Heating wires
- Overheat protection
- Wall mounted or floor stand
- IPX4 water proof
- Meas(mm):600x600x110
- Qty 20'/40'/40'HQ:1032/2160/2588pcs



NDFL788-(2N/3N/4N)

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
2N	650W	490x445x115	2400	2800
3N	1200W	700 x445x115	1700	2020
4N	1800W	910x445x115	1310	1540

General features:

- Panel Convactor
- Thermostat control
- Over heating protection



NDFL788-(2R/3R/4R)

- With LCD display window



NDFL-1202(2/3/4)

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
2	650W	490x445x115	2400	2800
3	1200W	700 x445x115	1700	2020
4	1800W	910x445x115	1310	1540

General features:

- Panel Convactor
- Thermostat control
- Over heating protection

NDFL789-(3N/4N)

FIN	POWER	MEAS(mm)	PCS/40'	PCS/40'HQ
3N	750W	790x255x115	2500	2950
4N	1500W	1030 x255x115	1950	2240

General features:

- Panel Convactor
- Thermostat control
- Over heating protection



CH-2000D STAND

CH-2000D TIMER

CH-2000D STAND/TIMER

- 3 different heat settings:750W/1250W/2000W
- Adjustable thermostat control
- 24 hour segmented dial timer (only for CH-2000D TIMER)
- Operating switches with indication lights
- Frost guard protection
- Overheat safety cut-out
- Floor standing or wall mounting
- Meas(mm):720x140x475
- Qty/40': 1260 PCS Qty/40'HQ: 1438 PCS



CH-2000B TURBO

CH-2000B TIMER & TURBO

CH-2000B TURBO/TIMER & TURBO

- 3 different heat settings:750W/1250W/2000W
- Adjustable thermostat control
- 24 hour segmented dial timer (only for CH-2000B TIMER & TURBO)
- Fan forced hot/cool air system
- Operating switches with indication lights
- Fan forced hot/cool air system
- Frost guard protection
- Overheat safety cut-out
- Floor standing or wall mounting
- Meas(mm):640x140x450
- Qty/40': 1470 PCS Qty/40'HQ: 1650 PCS



CH-2000D TURBO

CH-2000D TIMER & TURBO

CH-2000D TURBO/TIMER & TURBO

- 3 different heat settings:750W/1250W/2000W
- Adjustable thermostat control
- 24 hour segmented dial timer (only for CH-2000D TIMER & TURBO)
- Fan forced hot/cool air system
- Operating switches with indication lights
- Frost guard protection
- Overheat safety cut-out
- Floor standing or wall mounting
- Meas(mm):720x140x475
- Qty/40': 1260 PCS Qty/40'HQ: 1438 PCS



CL-2000L

CL-2000L TIMER & TURBO

CL-2000L/TIMER & TURBO

- 3 different heat settings:750W/1250W/2000W
- Adjustable thermostat control
- 24 hour segmented dial timer (only for CH-2000B TIMER & TURBO)
- Fan forced hot/cool air system
- Operating switches with indication lights
- Fan forced hot/cool air system
- Frost guard protection
- Overheat safety cut-out
- Floor standing or wall mounting
- Meas(mm):640x140x450
- Qty/40': 1270 PCS Qty/40'HQ: 1440 PCS



CH-2000B STAND

CH-2000B TIMER

CH-2000B STAND/TIMER

- 3 different heat settings:750W/1250W/2000W
- Adjustable thermostat control
- 24 hour segmented dial timer (only for CH-2000B TIMER)
- Operating switches with indication lights
- Frost guard protection
- Overheat safety cut-out
- Floor standing or wall mounting
- Meas(mm):640x140x450
- Qty/40': 1470 PCS Qty/40'HQ: 1650 PC



NDL200-40

NDL200-40T

NDL200-40/NDL200-40T

- 3 different heat settings:750W/1250W/2000W
- Three power outputs setting
- Adjustable thermostat
- Over heating protection
- Wall mounted or floor stand
- With 24 hours timer(NDL200-40T)
- Meas(mm):665x175x485
- Qty 20'/40'/40'HQ:500/1050/1236pcs



NDY-15BRC

- Power:1500W
- Three power outputs setting
- Adjustable thermostat
- Over heating protection
- With remote control
- With LED display
- Wall mounted or floor stand
- Meas(mm):750x120x635
- Qty 20'/40'/40'HQ:525/1053/1242pcs

NDY-20BRC

- Power:2000W
- Three power outputs setting
- Adjustable thermostat
- Over heating protection
- With remote control
- With LED display
- Wall mounted or floor stand
- Meas(mm):850x120x635
- Qty 20'/40'/40'HQ:474/948/1114pcs



NDY-600

- Power:600W
- Two power outputs setting
- Adjustable thermostat
- Over heating protection
- Meas(mm):620x100x300
- Qty 20'/40'/40'HQ:1638/3325/3762pcs

NDY-1200

- Power:1200W
- Two power outputs setting
- Adjustable thermostat
- Over heating protection
- Meas(mm):870x100x300
- Qty 20'/40'/40'HQ:1092/2371/2670pcs



NDY-18

- Power:1800W
- Three power outputs setting
- Adjustable thermostat
- Over heating protection
- Wall mounted or floor stand
- Meas(mm):890x120x595
- Qty 20'/40'/40'HQ:429/858/1014pcs

NDY-18RC

- Power:1800W
- Three power outputs setting
- Adjustable thermostat
- Over heating protection
- Wall mounted or floor stand
- With remote control
- 24 hours timer
- Meas(mm):890x120x595
- Qty 20'/40'/40'HQ:429/858/1014pcs



QH-1200F

- 2 heat settings:600W/1200W
- 2 quartz heating elements
- Pull chain control
- Tilt adjustable wall mounting
- Meas(mm):605x130x145
- Qty/20':2220pcs Qty/40':4500pcs Qty/40'HQ:5160pcs

QH-1200Q

- Power:600W/1200W
- 2 heating elements
- Pull chain control
- Tilt adjustable wall mounting
- Meas(mm):565x160x130
- Qty/20':1840pcs Qty/40':3800pcs Qty/40'HQ:5230pcs



NSB-60A

- 2 heat settings: 300W/600W
- 2 quartz heating elements
- Safety tip-over switch
- With integral handle
- Meas(mm):285x180x385
- Qty/20':1500pcs Qty/40'HQ:3402pcs

NSB-80D

- 2 heat settings: 400W/800W
- 2 quartz heating element
- Safety tip-over switch
- Integral handle
- Meas(mm):308x140x380
- Qty/20':1350pcs Qty/40'HQ:3500pcs



NSB-80C

- 2 heat settings: 400W/800W
- 2 quartz heating elements
- Safety tip-over switch
- With integral handle
- Meas(mm):315x170x400
- Qty/20':1200pcs Qty/40'HQ:3096pcs

NFG-9

- 2 heat settings: 400W/800W
- 2 quartz heating elements
- Safety tip-over switch
- With integral handle
- Meas(mm):284x168x410
- Qty/20':1350pcs Qty/40'HQ:3060pcs

Quartz Heater



QH-2200N

- Ceramic heating element
- Power: 1100W/2200W
- Safety tip-over switch
- Metal housing
- Meas(mm): 345x195x420
- Qty/20': 1000pcs Qty/40'HQ: 2280pcs



NFG-6

- 2 heat settings: 300W/600W
- 2 quartz heating elements
- Safety tip-over switch
- With integral handle
- Meas(mm): 245x100x345
- Qty/20': 1350pcs Qty/40'HQ: 7440pcs



NFG-11

- 3 different heat settings: 300W/600W/900W
- 3 quartz heating elements
- Safety tip-over switch
- Integral handle
- Foldway base
- Meas(mm): 315x110x470
- Qty/40'HQ: 3800pcs



LX-1500

- 2 heat settings: 500W/1500W
- 2 quartz heating elements
- Safety tip-over switch
- Meas(mm): 560x190x320
- Qty/20': 823pcs Qty/40'HQ: 2016pcs



QH-1200B

- 2 heat settings: 600W/1200W
- 2 quartz heating elements
- Safety tip-over switch
- Wide angle oscillation
- Meas(mm): 245x190x745
- Qty/20': 700pcs Qty/40'HQ: 1652pcs



FG1501

- 2 heat settings: 400W/800W/1200W
- 2 quartz heating elements
- Safety tip-over switch
- With integral handle
- Meas(mm): 300x185x760
- Qty/20': 460pcs Qty/40'HQ: 1100pcs



NDF666

- Patio heater with IP44 water proof
- Power: 750W/1250W/2000W
- Pull chain control
- Tilt adjustable wall mounting
- Safety tip-over switch
- Meas(mm): 620x260x325
- Qty/20': 520pcs Qty/40': 1100pcs Qty/40'HQ: 1400pcs



NDF668

- Patio heater with IP44 water proof
- Power: 750W/1250W/2000W
- Pull chain control
- Tilt adjustable wall mounting
- Safety tip-over switch
- Meas(mm): 595x260x325
- Qty/20': 580pcs Qty/40': 1200pcs Qty/40'HQ: 1500pcs



NDW666

- Patio heater with IP44 water proof
- Power: 750W/1250W/2000W
- Pull chain control
- Tilt adjustable
- Safety tip-over switch
- Meas(mm): 530x220x560
- Qty/20': 450pcs Qty/40': 920pcs Qty/40'HQ: 1050pcs



NDW668

- Patio heater with IP44 water proof
- Power: 750W/1250W/2000W
- Pull chain control
- Tilt adjustable
- Safety tip-over switch
- Meas(mm): 530x240x560
- Qty/20': 416pcs Qty/40': 840pcs Qty/40'HQ: 960pcs



YS-10

YS-10T

YS-10

- 2 heat settings:400W/800W
- Meas(mm):400x185x365
- Qty/40':2130pcs Qty/40'HQ: 2470pcs

YS-10T

- 2 heat settings:400W/800W
- With fan
- Meas(mm):400x185x365
- Qty/40':2130pcs Qty/40'HQ: 2470pcs



YS-12

FG-12

YS-12

- 3 heat settings:400W/800W/1200W
- Wide angle oscillation
- Meas(mm):350x150x540
- Qty/20':1000pcs Qty/40'HQ:2300pcs

FG-12

- 3 heat settings:400W/800W/1200W
- Wide angle oscillation
- Meas(mm):315x160x590
- Qty/20':1000pcs Qty/40'HQ:2300pcs



HM-12

HM-12R

HM-12

- 3 heat settings: 400W/800W/1200W
- Wide angle oscillation
- Meas(mm):380x180x625
- Qty/20':650pcs Qty/40'HQ: 1670pcs

HM-12R

- 3 heat settings: 400W/800W/1200W
- Wide angle oscillation
- Meas(mm):380x180x625
- Qty/20':650pcs Qty/40'HQ: 1670pcs



NSB-120Y

NSB-120R

NSB-120Y

- 3 heat settings: 400W/800W/1200W
- Wide angle oscillation
- Meas(mm):350x150x650
- Qty/40':1580pcs Qty/40'HQ:1840pcs

NSB-120R

- 3 heat settings:400W/800W/1200W
- Wide angle oscillation
- Meas(mm):350x150x650
- Qty/40':1580pcs Qty/40'HQ:1840pcs



YQ-12

YQ-12R

YQ-12

- 3 different heat settings: 400W/800W/1200W
- Wide angle oscillation
- Meas(mm):350x165x580
- Qty/20':900pcs Qty/40'HQ:2100pcs

YQ-12R

- 3 different heat settings: 400W/800W/1200W
- Wide angle oscillation
- Meas(mm):350x165x580
- Qty/20':900pcs Qty/40'HQ:2100pcs



TS-12

TS-12R

TS-12

- 3 heat settings: 400W/800W/1200W
- Wide angle oscillation
- Meas(mm):380x170x645
- Qty/20':730pcs Qty/40'HQ:1700pcs

TS-12R

- 3 heat settings: 400W/800W/1200W
- Wide angle oscillation
- Meas(mm):380x170x645
- Qty/20':730pcs Qty/40'HQ:1700pcs



NSB-160

NSB-160R

NSB-160

- 4 different heat settings: 400W/800W/1200W/1600W
- Wide angle oscillation
- Giftbox:350x165x580mm
- Qty/20':750pcs Qty/40'HQ:1800pcs

NSB-160R

- 4 different heat settings: 400W/800W/1200W/1600W
- Wide angle oscillation
- Giftbox:350x165x580mm
- Qty/20':750pcs Qty/40'HQ:1800pcs



TS-16

TS-16R

TS-16

- 4 different heat settings: 400W/800W/1200W/1600W
- Wide angle oscillation
- Giftbox:350x170x675mm
- Qty/20':700pcs Qty/40'HQ:1600pcs

TS-16R

- 4 different heat settings: 400W/800W/1200W/1600W
- Wide angle oscillation
- Giftbox:350x170x675mm
- Qty/20':700pcs Qty/40'HQ:1600pcs



PTC-903

PTC-903B

PTC-903

- Rated power:750W/1500W
- Cool/Warm/Hot wind for selection
- Overheat protection
- Safety tip-over switch
- G.W./N.W.:10.8KGS/9.0KGS
- Color box meas: 205x150x295mm
- Outer carton meas: 650x225x615mm, 6pcs/ctn
- Quantity:1940pcs/20',3920pcs/40', 4560pcs/40'HQ

PTC-903B

- Rated power:750W/1500W
- Cool/Warm/Hot wind for selection
- Wide angle oscillation
- Overheat protection
- Safety tip-over switch
- G.W./N.W.:13.2KGS/12.0KGS
- Color box meas: 230x175x325mm
- Outer carton meas: 475x365x675mm, 6pcs/ctn
- Quantity:1880pcs/20',3800pcs/40', 4390pcs/40'HQ



PTC-905

PTC-905B

PTC-905

- Rated power:750W/1500W
- Cool/warm/hot wind
- Safety tip-over switch
- Power indicator light
- Overheating protection
- G.W./N.W.:13.4KGS/10.4KGS
- Color box meas: 200x175x275 mm
- Outer carton meas: 415x365x570mm, 8pcs/ctn
- Quantity:2550pcs/20',5180pcs/40', 6040pcs/40'HQ

PTC-905B

- Rated power:750W/1500W
- Cool/warm/hot wind
- Safety tip-over switch
- Power indicator light
- Wide angle oscillation
- Overheating protection
- G.W./N.W.:15.6KGS/12.8KGS
- Color box meas:200x175x300mm
- Outer carton meas:415x365x620mm, 8pcs/ctn
- Quantity:2420pcs/20',4890pcs/40', 5470pcs/40'HQ



PTC-902

PTC-902B

PTC-902

- Rated power:750W/1500W
- Cool/Warm/Hot wind for selection
- Overheat protection
- Safety tip-over switch
- G.W./N.W.:10.8KGS/9.0KGS
- Color box meas: 205x150x295mm
- Outer carton meas: 650x225x615mm, 6pcs/ctn
- Quantity:1940pcs/20',3920pcs/40', 4560pcs/40'HQ

PTC-902B

- Rated power:750W/1500W
- Cool/Warm/Hot wind for selection
- Wide angle oscillation
- Overheat protection
- Safety tip-over switch
- G.W./N.W.:13.2KGS/12.0KGS
- Color box meas: 230x175x325mm
- Outer carton meas: 475x365x675mm, 6pcs/ctn
- Quantity:1880pcs/20',3800pcs/40', 4390pcs/40'HQ



PTC-908

PTC-150B

PTC-908

- 2 heat settings:750W/1500W
- Cool/warm/hot wind for selection
- Overheat protection
- Tip-over switch
- Adjustable thermostat
- With carry handle
- Meas:175x155x225mm
- Qty/40'HQ:9768pcs

PTC-150B

- 2 heat settings:750W/1500W
- Cool/warm/hot wind for selection
- Overheat protection
- Tip-over switch
- Adjustable thermostat
- With carry handle
- Meas(mm):225x225x240
- Qty 20'/40'/40'HQ:2058/4272/5190pcs



NDQ1308

NDQ1302

NDQ1308

- 2 heat settings:900W/1500W
- Cool/warm/Hot wind for selection
- Overheat protection
- Tip-over switch
- Adjustable thermostat
- With carry handle
- Meas:175x160x240mm
- Qty/40'HQ:9200pcs

NDQ1302

- 2 heat settings:900W/1500W
- Cool/warm/Hot wind for selection
- Overheat protection
- Tip-over switch
- Adjustable thermostat
- With carry handle
- Meas:210x160x245mm
- Qty/40'HQ:4992pcs

Mini Fireplace



TNP-E3

TNP-E1

TNP-E3

- Two heating setting
- Power supply: 230V 50Hz 1500W
- PTC heating element
- Overheating protection
- Tip over protection
- Power indicator light
- Giftbox: 275x195x367mm
- Export Carton: 405x565x382mm, 4pcs/ctn
- G.W.:11.5kgs N.W.:10.5kgs
- Qty 20'/40'/40'HQ:1224/2608/3056pcs

TNP-E1

- Two heating setting
- Power supply: 230V 50Hz 1500W
- PTC heating element
- Overheating protection
- Tip over protection
- Power indicator light
- Giftbox: 275x195x367mm
- Export Carton: 405x565x382mm, 4pcs/ctn
- G.W.:11.5kgs N.W.:10.5kgs
- Qty 20'/40'/40'HQ:1224/2608/3056pcs



FH-20



FH-20A

FH-20

- 2 heat settings:1000W/2000W
- Cool fan for summer use
- Power indicator light
- Adjustable thermostat
- Thermal automatic cut-out
- Overheating protection
- Safety thermal fuse built in
- G.W.:1.3kg N.W.:1.2kg
- Giftbox:230x208x295mm
- 6pcs carton:640x245x610mm
- Qty/20':1890pcs Qty/40':3880pcs
- Qty/40'HQ:4520pcs

FH-20A

- 2 heat settings:1000W/2000W
- Cool fan for summer use
- Power indicator light
- Adjustable thermostat
- Overheating safety cut-out
- Wide angle oscillation
- G.W.:1.45kg N.W.:1.18kg
- Giftbox:230x208x313mm
- 6pcs carton:640x245x645mm
- Qty/20':1740pcs Qty/40':3534pcs
- Qty/40'HQ:4100pcs



FH-03



FH-04

FH-03

- 2 heat settings:1000W/2000W
- Cool/warm/hot wind for selection
- Power indicator light
- Adjustable thermostat
- Overheating protection
- Safety thermal fuse built in
- Upright or low profile position
- G.W.:1.18kg N.W.:1.0kg
- Giftbox:232x140x270mm
- 6pcs carton:430x240x555mm
- Qty/20':2940pcs Qty/40':6420pcs
- Qty/40'HQ:7020pcs

FH-04

- 2 heat settings:1000W/2000W
- Cool/warm/hot wind for selection
- Power indicator light
- Adjustable thermostat
- Overheating protection
- Safety thermal fuse built in
- Upright or low profile position
- G.W.:1.15kg N.W.:1.0kg
- Giftbox:232x140x270mm
- 6pcs carton:430x240x555mm
- Qty/20':2940pcs Qty/40':6420pcs
- Qty/40'HQ:7020pcs



FH-A06



FH06

FH-A06

- 2 heat settings:1000W/2000W
- Cool/warm/hot wind for selection
- Power indicator light
- Adjustable thermostat
- Overheating protection
- Safety thermal fuse built in
- Integral carry handle
- G.W.:1.2kg N.W.:1.0kg
- Giftbox:245x122x286mm
- 6pcs carton:495x265x600mm
- Qty/20':2800pcs Qty/40':5600pcs
- Qty/40'HQ:6720pcs

FH06

- 2 heat settings:1000W/2000W
- Cool/warm/hot wind for selection
- Power indicator light
- Adjustable room thermostat
- Overheating protection
- Safety thermal fuse built in
- G.W.:1.41kg N.W.:1.2kg
- Giftbox:255x125x258mm
- 6pcs carton:390x270x530mm
- Qty/20':3000pcs Qty/40':6150pcs
- Qty/40'HQ:7000pcs



FH-15



FH202

FH-15

- 2 heat settings:1000W/2000W
- Cool/warm/hot wind for selection
- Power indicator light
- Adjustable thermostat
- Overheating protection
- Safety thermal fuse built in
- G.W.:1.5kg N.W.:1.2kg
- Giftbox:265x130x275mm
- 6pcs carton:410x275x560mm
- Qty/20':2856pcs Qty/40':5736pcs
- Qty/40'HQ:6730pcs

FH202

- 2 heat settings:1000W/2000W
- Cool/warm/hot wind for selection
- Metal body
- Power indicator light
- Adjustable thermostat
- Automatic control temperature
- Overheating protection
- Safety thermal fuse built in
- G.W.:1.05kg N.W.:0.85kg
- Giftbox:187x135x237mm
- 6pcs carton:420x197x489mm
- Qty/20':1950pcs Qty/40':3900 pcs
- Qty/40'HQ: 4740pcs



NDY20AR

- 2 heat settings:1000W/2000W
- Cool/warm/hot wind for selection
- Wall mounted or tabled
- Overheat protection
- Automatic oscillating louvers
- 7.5 hours timer
- With remote control
- With LED display
- Meas:500x125x190mm
- Qty/40'HQ:4896pcs



NDY20BR

- 2 heat settings:1000W/2000W
- Cool/warm/hot wind for selection
- Wall mounted or tabled
- Overheat protection
- Automatic oscillating louvers
- 7.5 hours timer
- With remote control
- With LED display
- Meas:555x155x235mm
- Qty/40'HQ:2800pcs



NDY20CR

- 2 heat settings:1000W/2000W
- Cool/warm/hot wind for selection
- Wall mounted or tabled
- Overheat protection
- Automatic oscillating louvers
- 7.5 hours timer
- With remote control
- With LED display
- Meas:555x155x235mm
- Qty/40'HQ:2800pcs



NDY20DR

- 2 heat settings:1000W/2000W
- Cool/warm/hot wind for selection
- Wall mounted or tabled
- Overheat protection
- Automatic oscillating louvers
- 7.5 hours timer
- With remote control
- With LED display
- Meas:645x159x245mm
- Qty/40'HQ:2400pcs



NDY20ER

- Cool/warm/hot wind for selection
- Automatic oscillating louvers
- Overheat protection, Wall mounted or tabled
- Manual and remote control available
- Rated power:1000w/2000w
- Electrical source indicator light
- 7.5 hours timer
- G.W.:4.8kgs N.W.:3.8kgs
- Giftbox:680x148x255mm
- 4pcs carton: 695x306x525mm
- Qty/40':2160pcs Qty/40'HQ:2528pcs



NDFK968

- 2 heat settings: 500W/1000W
- Meas(mm): 400x370x490
- Qty/40': 820pcs Qty/40'HQ: 960pcs



NDFK668

- 2 heat settings: 500W/1000W
- Meas(mm): 400x370x490
- Qty/40': 820pcs Qty/40'HQ: 960pcs



NDFK667

- 2 heat settings: 500W/1000W
- Meas(mm): 400x370x490
- Qty/40': 820pcs Qty/40'HQ: 960pcs



NDFK059

- 2 heat settings: 500W/1000W
- Meas(mm): 400x370x490
- Qty/40': 820pcs Qty/40'HQ: 960pcs



NDFK41

- 2 heat settings: 500W/1000W
- Meas(mm): 400x370x490
- Qty/40': 820pcs Qty/40'HQ: 960pcs



NDFK32

- 2 heat settings: 500W/1000W
- Meas(mm): 400x370x490
- Qty/40': 820pcs Qty/40'HQ: 960pcs



NDFK966

- 2 heat settings: 500W/1000W
- Meas(mm): 400x370x490
- Qty/40': 820pcs Qty/40'HQ: 960pcs



NDFK793R

- 2 heat settings: 500W/1000W
- Meas(mm): 400x370x560
- Qty/40': 740pcs Qty/40'HQ: 870pcs



NDFK669

- 2 heat settings: 500W/1000W
- Meas(mm): 400x370x490
- Qty/40': 820pcs Qty/40'HQ: 960pcs



NDFK8661

- 2 heat settings: 500W/1000W
- Meas(mm): 400x370x490
- Qty/40': 820pcs Qty/40'HQ: 960pcs



NDFK1065

- 2 heat settings: 500W/1000W
- Meas(mm): 400x370x490
- Qty/40': 820pcs Qty/40'HQ: 960pcs



NDFK046

- 2 heat settings: 400W/800W
- Meas(mm): 380x355x395
- Qty/40': 1170pcs Qty/40'HQ: 1380pcs



NDFK670

- 2 heat settings: 400W/800W
- Meas(mm): 365x355x380
- Qty/40': 1170pcs Qty/40'HQ: 1380pcs



JHS-800H

- 2 heat settings: 400W/800W
- Meas(mm): 330x330x525
- Qty/40': 1080pcs Qty/40'HQ: 1200pcs



NDFK1207

- 2 heat settings: 300W/600W
- Meas(mm): 260x240x420
- Qty/40': 1170pcs Qty/40'HQ: 2800pcs



NDFK1180

- 2 heat settings: 300W/600W
- Meas(mm): 365x355x380
- Qty/40': 1170pcs Qty/40'HQ: 1500pcs



NDFK036

- 2 heat settings: 400W/800W
- Meas(mm): 320x320x500
- Qty/40': 1170pcs Qty/40'HQ: 1380pcs



JHS-500C

- 1 heat setting: 500W
- Double safety devices
- Wide angle oscillation
- Meas(mm): 240x240x360
- Qty/40': 2640pcs Qty/40'HQ: 3000pcs



JHS-500E

- 1 heat setting: 500W
- Double safety devices
- Wide angle oscillation
- Meas(mm): 240x240x360
- Qty/40': 2640pcs Qty/40'HQ: 3000pcs



JHS-500Z

- 1 heat setting: 500W
- Double safety devices
- Wide angle oscillation
- Meas(mm): 245x245x365
- Qty/20': 1242pcs Qty/40'HQ: 2826pcs



FGT16

- 2 heat settings: 400W/800W
- Meas(mm): 330x330x525
- Qty/40': 1080pcs Qty/40'HQ: 1200pcs



NDFK051

- 2 heat settings: 400W/800W
- Meas(mm): 330x330x525
- Qty/40': 1080pcs Qty/40'HQ: 1200pcs



DH-112

- 2 heat settings: 400W/800W
- Meas(mm): 420x230x390
- Qty/40': 1500pcs Qty/40'HQ: 1750pcs



NDFK672



NDFK779



NDFK1231

NDFK672

- 2 heat settings: 500W/1000W
- Meas(mm): 620x320x415
- Qty/40': 730pcs Qty/40'HQ: 830pcs

NDFK779

- 2 heat settings: 500W/1000W
- Meas(mm): 620x320x415
- Qty/40': 730pcs Qty/40'HQ: 830pcs

NDFK1231

- 2 heat settings: 500W/1000W
- Meas(mm): 620x320x415
- Qty/40': 730pcs Qty/40'HQ: 830pcs



TALLEN[®] VECOO[®]

Ningbo Cixi Import And Export Holdings Co., Ltd.
Ningbo Vecoo Electric Appliances Co., Ltd.

Office Add.: Room2005-Hengyuan Plaza-A.No.1988
East Beisanhuan Rd.Cixi, Ningbo, China
P.C.: 315300

Tel: +86-574-63886827, 63032532

Fax: +86-574-63032651

E-mail:bobka@cnool.net

<http://www.vecoo.com>